

> [Linux Reviews](#) > [Tips and Tricks](#) >

alias - How to make aliases for frequently used commands

v2.1 (no), xiando

alias allows you to define shortcuts and synonyms for commonly used shell commands.

The basic usage is:

```
alias newcommand='yourcommand -arguments'
```

If you want to start [aterm](#) according to your preferences with the command term, do something like:

```
alias term='aterm -ls -fg gray -bg black'
```

If you want a quick alias like ll for a more informative file listing:

```
ls -al --color=yes
```

Starting alias without any options lists the current aliases:

```
alias
alias ls='ll'
alias ls -al --color=yes
alias term='aterm -ls -fg gray -bg black'
```

Use unalias to remove an alias.

```
unalias term
```

You can also make aliases for existing commands. If you want ls to show colors by default, do:

```
alias ls='ls --color=yes'
```

These aliases can be put in your login script (.bash_profile or .profile depending on what shell you are using).

Gentoo Linux tips

```
alias aemerge='ACCEPT_KEYWORDS=""~x86" emerge'
```

Alias with variables

You can **not** make aliases with variables. But you can make functions, having a function in your .profile/.bashrc will work just like an alias. To use ssh to copy files to a location on a server you can use

```
sendpic () { scp $* mina@foo.bar.ca:/www/misc/Pictures/; }
```

thanks to mina

Copyright (c) 2000-2004 Øyvind Sæther. Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled ["GNU Free Documentation License" <http://www.gnu.org/licenses/fdl.html>].

> [Linux Reviews](#) > [Tips and Tricks](#) >
alias - How to make aliases for frequently used commands